

110° Ceramic Flat Fan Nozzle Table

	PSI	Capacity Per Nozzle		Gallons/Acre 20" Spacing							
		GPM	Oz/Min	4MPH	5MPH	6MPH	7MPH	8MPH	9MPH	10MPH	12MPH
NSFC11015-CSK	15	0.092	12	6.8	5.5	4.6	3.9	3.4	2.7	2.3	2
	20	0.11	14	8.2	6.5	5.4	4.7	4.1	3.3	2.7	2.3
	30	0.13	17	9.7	7.7	6.4	5.5	4.8	3.9	3.2	2.8
	40	0.15	19	11.1	8.9	7.4	6.4	5.6	4.5	3.7	3.2
	50	0.17	22	12.6	10.1	8.4	7.2	6.3	5	4.2	3.6
	60	0.18	23	13.4	10.7	8.9	7.6	6.7	5.3	4.5	3.8
NSFC11002-CSK	15	0.12	15	8.9	7.1	5.9	5.1	4.5	3.6	3	2.5
	20	0.14	18	10.4	8.3	6.9	5.9	5.2	4.2	3.5	3
	30	0.17	22	12.6	10.1	8.4	7.2	6.3	5	4.2	3.6
	40	0.2	26	14.9	11.9	9.9	8.5	7.4	5.9	5	4.2
	50	0.22	28	16.3	13.1	10.9	9.3	8.2	6.5	5.4	4.7
	60	0.24	31	17.8	14.3	11.9	10.2	8.9	7.1	5.9	5.1
NSFC11003-CSK	15	0.18	23	13.4	10.7	8.9	7.6	6.7	5.3	4.5	3.8
	20	0.21	27	15.6	12.5	10.4	8.9	7.8	6.2	5.2	4.5
	30	0.26	33	19.3	15.4	12.9	11	9.7	7.7	6.4	5.5
	40	0.3	38	22	17.8	14.9	12.7	11.1	8.9	7.4	6.4
	50	0.34	44	25	20	16.8	14.4	12.6	10.1	8.4	7.2
	60	0.37	47	27	22	18.3	15.7	13.7	11	9.2	7.8
NSFC11004-CSK	15	0.24	31	18	14.3	11.9	10.2	8.9	7.1	5.9	5.1
	20	0.28	36	21	16.6	13.9	11.9	10.4	8.3	6.9	5.9
	30	0.35	45	26	21	17.3	14.9	13	10.4	8.7	7.4
	40	0.4	51	30	24	19.8	17	14.9	11.9	9.9	8.5
	50	0.45	58	33	27	22	19.1	16.7	13.4	11.1	9.5
	60	0.49	63	36	29	24	21	18.2	14.6	12.1	10.4